

# ØS-Hilti Calculation data for Flexible Light Support Bracket fitted with Hilti S-BT ØI-RD-CB-EN-0024

Article	Description	Material	Thickness (mm)	Application	Fixing Bolt(s)
1371720	Flexi Bracket for Light Fitting Support OE100-AH	AISI 316L	2.5	Flexible Light support bracket	2


## PRODUCT AND APPLICATION



## ALLOWABLE LOADS

FIT	+/-Fz,Rk [kN]
Form lock	0.20
Friction lock	0.20

## ORIENTATION



## ADDITIONAL INFORMATION

Form lock refers to a bolt set up that do not depend on friction to secure the channel to the starter bracket.  
Friction lock refers to a bolt set up that depends on friction to secure the channel to the starter bracket.

The data results shown above are calculated set up with form lock and friction lock. NB! Should always be used in pairs for light support.

Can be used for universal support of equipment.

The calculated loadings shown include a safety factor and are the recommended maximum loadings for the combination of the part(s) and the fixing(s) shown for typical applications. Certain scenarios may allow for higher loadings to be considered.

We recommend to use a calibrated torque tool to ensure correct torque on the connection.

Bolts: Hilti S-BT-MR-M10/15 SN6

Scan QR code for fitting instructions for S-BT

